

MasoSine Process Pumps

Telephone: +49 (0) 7062 95600

Fax: +49 (0) 7062 64593

E-Mail: info@masosine.de

www.masosine.de

The information contained in this document is believed to be correct, but the Watson-Marlow Fluid Technology Group accepts no liability of any errors it contains and reserves the right to alter specifications without notice.

	Certa 100	Certa 200	Certa 250	Certa 300	Certa 400	Certa 500	Certa 600
max. pressure	145 PSI 10 bar	145 PSI 10 bar	217 PSI 15 bar	217 PSI 15 bar	217 PSI 15 bar	217 PSI 15 bar	217 PSI 15 bar
max. speed	1000 rpm	1000 rpm	800 rpm	600 rpm	600 rpm	600 rpm	600 rpm
Temp.	-4F -20°C +212 F +100°C	-4F -20°C +212 F +100°C	-4F -20°C +212 F +100°C	-4F -20°C +212 F +100°C	-4F -20°C +212 F +100°C	-4F -20°C +212 F +100°C	-4F -20°C +212 F +100°C
Ambient temp.	+10.5 F -12°C +104 F +40°C	+10.5 F -12°C +104 F +40°C	+10.5 F -12°C +104 F +40°C	+10.5 F -12°C +104 F +40°C	+10.5 F -12°C +104 F +40°C	+10.5 F -12°C +104 F +40°C	+10.5 F -12°C +104 F +40°C
Weight	35,4 lb 16 kg	46,5 lb 21 kg	88,3 lb 40 kg	147 lb 67 kg	254 lb 115 kg	437 lb 198 kg	546 lb 238 kg



2006/42/EC
DIN 12100,1-2
97 / 23 / EG
DIN 60204-1



< 70 dB-A @1m

QUICK START GUIDE MASOSINE PUMPS



www.masosine.com

Innovation in Full Flow

